Технический паспорт
Выпуск: 21 апреля 2022
Количество страниц: 2

METYLAN

Клей для стыков и подклейки обоев

Для настенных покрытий

СВОЙСТВА

- Универсальный ремонтный клей
- Идеален для склеивания краёв и стыков
- Подходит для всех видов обоев и оснований
- Клеит даже винил с винилом
- После высыхания становится прозрачным

ОБЛАСТИ ПРИМЕНЕНИЯ

Предназначен для склеивания обоев в области швов и стыков, включая несоприкасающиеся основания. Применяется также для ремонта всех видов обоев и для склеивания внахлёст по внутренним и внешним углам, например, в оконных откосах.

ПРИМЕНЕНИЕ

Специально разработанная формула для ремонтного применения позволяет легко и быстро устранить небольшие повреждения обоев и настенных покрытий.
Нанести Metylan Ovalit клей для швов и ремонта на склеиваемую поверхность, равномерно распределить и прижать.

ОЧИСТКА ИНСТРУМЕНТОВ

Клей Metylan для швов и ремонта высыхает, становясь прозрачным.

Во избежание различий в блеске и проблем с покрытием, остатки клея следует немедленно осторожно удалить с лицевой стороны покрытия влажной губкой и чистой водой.

Инструменты очистить холодной водой сразу после использования.

ХРАНЕНИЕ

Хранить тару плотно закрытой и в защищённом от мороза месте.

УПАКОВКА

Обозначение	Размер упаковки
MNR40	40 тюбиков по 60 г

РЕКОМЕНДАЦИИ ПО БЕЗОПАСНОСТИ

Рекомендуется перед началом использования ознакомиться с актуальным паспортом безопасности, чтобы получить информацию о мерах предосторожности и советах по технике безопасности.

Паспорт безопасности доступен на сайте: www.mysds.henkel.com

Информация для аллергиков доступна по телефону: 0049 (0)211 797 0 (указать ключевое слово Notfall — «чрезвычайная ситуация»).

РЕКОМЕНДАЦИИ ПО УТИЛИЗАЦИИ

Небольшие засохшие остатки можно утилизировать как бытовые или производственные отходы. Крупные количества подлежат отдельной утилизации. Пустая упаковка подлежит переработке.
Европейский код отходов указан в паспорте безопасности.

ТЕХНИЧЕСКИЕ ДАННЫЕ

Основной компонент:	пластиковая дисперсия без пластификаторов
Плотность:	1,1 г/см³
pH:	около 7
Открытое время:	до 10 минут (в зависимости от основания и условий окружающей среды)
Температура нанесения:	не ниже +10 °C, рекомендовано +18 °C
Прочность склеивания:	устойчива ко всем обычным внутренним воздействиям и нагрузкам
Срок хранения:	12 месяцев

При составлении данного технического паспорта мы учли текущий уровень технического развития в соответствии с нашим опытом.
Все предыдущие версии утрачивают свою силу с момента выхода настоящего технического паспорта.

К сведению: приведённые выше данные являются лишь общими рекомендациями.
Поскольку условия применения и использования материалов находятся вне нашего контроля,
а также ввиду большого разнообразия материалов, мы настоятельно рекомендуем предварительно проводить собственные испытания.
Ответственность за конкретные результаты применения на основании данного технического паспорта не возлагается..

Henkel AG & Co. KGaA – Клеи для потребителей, Германия
Henkelstraße 67, D-40589 Düsseldorf Почтовый ящик: D-40191 Düsseldorf
Тел. +49 (0) 211/ 797-5800
www.metylan.de

Henkel & Cie. AG
Salinenstrasse 61
CH-4133 Pratteln1
Тел.: 061 825 7000

Данный документ был создан и электронно подписан компанией Henkel

Technical Data Sheet
Issue Date: April 21, 2022
Number of Pages: 2

METYLAN

Seam and Repair Adhesive

Dispersion adhesive – for wallcoverings

PROPERTIES

- Universal repair adhesive
- Ideal for bonding edges and corners
- Suitable for all types of wallpapers and substrates
- Bonds even vinyl to vinyl
- Dries transparent

APPLICATION AREAS

Designed for bonding wallpaper seams and joints, including detached substrates.

Also used for repairing all types of wallpapers and for overlapping bonding on internal and external corners, such as window reveals.

APPLICATION

The specially formulated adhesive is intended for repair use, allowing quick and easy correction of minor damage to wallpapers and wall coverings.
Apply Metylan Ovalit Seam and Repair Adhesive to the bonding area, spread evenly, and press firmly.

TOOL CLEANING

Metylan Seam and Repair Adhesive dries transparent.

To avoid differences in gloss or finishing problems, any adhesive residues must be carefully removed immediately from the front of the wallcovering using a damp sponge and clean water.

Clean tools with cold water immediately after use.

STORAGE

Store the container tightly closed and in a frost-free environment.

PACKAGING

Product Code	Package Size
MNR40	40 tubes of 60g each

SAFETY RECOMMENDATIONS

It is recommended to read the current safety data sheet before use for information on safety precautions and handling instructions.

The safety data sheet is available at: www.mysds.henkel.com

Information for individuals with allergies is available by phone:

+49 (0)211 797 0 (keyword: Notfall – “emergency”).

DISPOSAL INSTRUCTIONS

Small dried remnants can be disposed of with household or industrial waste.
Larger amounts must be disposed of separately.
Empty packaging should be recycled.
The European Waste Code (EWC) is listed in the safety data sheet.

TECHNICAL DATA

Main Component:	Plastic dispersion without plasticizers
Density:	1.1 g/cm³
pH:	approx. 7
Open Time:	up to 10 minutes (depending on substrate and ambient conditions)
Application Temperature:	not below +10 °C, +18 °C recommended
Bonding Strength:	Resistant to all common interior influences and stresses
Shelf Life:	12 months

When preparing this technical data sheet, the current state of technical development has been considered in accordance with our experience.
All previous versions lose validity upon the release of this document.

Note: The above information is only general guidance.
Since the conditions of application and use of the material are beyond our control and due to the wide variety of materials, we strongly recommend conducting your own preliminary tests.
No liability is assumed for specific application results based on this technical data sheet.

Henkel AG & Co. KGaA – Consumer Adhesives, Germany
Henkelstraße 67, D-40589 Düsseldorf
P.O. Box: D-40191 Düsseldorf
Tel.: +49 (0) 211 / 797-5800
www.metylan.de

Henkel & Cie. AG
Salinenstrasse 61
CH-4133 Pratteln 1
Phone: +41 (0)61 825 7000

This document was created and electronically signed by Henkel.